©	EMERGENCY EYEWASH 형 SC380
	Pedestal emergency eyewash
	Floor emergency eyewash.
	\cdot High water flow and low water pressure with total way out value.
	· Instant automatic opening activated by lateral lever or foot pedal.
	Double aerated jet with dust cover.
	· Green color RAL 6029.
	 Suitable for industries, laboratories and generally where there is risk of personal damages from fire, acids, chemical reactants, petroleum products, radioactive materials or other contaminants. CE conformity.
100	
	TECHNICAL DATA
	Eyewash basin made of green polypropylene.
le l	 Manufactured in zinc galvanized steel covered with epoxy paint. Connecting parts in brass.
8	 Water pressure, minimum 0,2 MPa – maximum 0,5 MPa.
la l	• Water flow: 14 l/min \pm 10% .
8	Water inlet dimension: 1/2".
	Outlet dimension: 1+1/4".
	· Dimensions: 1020 mm high, basin Ø 260 mm.
	TECHNICAL DRAWING
SUGGESTED TEXT FOR PRESCRIPTION	
NOFER or similar floor emergency eyewash. Instant automatic	
opening activated by lateral lever or foot pedal. Manufactured in	130 INLET 1/2 " F
zinc galvanized steel covered with green epoxy paint. Eyewash basin made of green polypropylene. Dimensions: 1020 mm high,	
basin Ø 260 mm.	<u> の UTLET 1-1/4</u> " F
	Ø260
	Dimensions in mm
NOFER S.L.	
Avenida de la fama, 118 08940 · Cornellà de Llobregat (Barcelona) Tel +34 934 742 423 · Fax +34 934 743 548 export@nofer.com · www.nofer.com	PER SC700 SC710 SC380SS SC820 SC800 SC730

.0565 - This specifications can be modified and/or rectified due to manufacture requirements